Application No.	Applicant(s)	
10/009.982	NAKASHIMA ET AL	
Examiner	Art Unit	
Susan S. Lee	2852	
S (OR REMAINS) CLOSED b) or other appropriate come RIGHTS. This application is 3 and MPEP 1308.	in this application. If not included nunication will be mailed in due course. T	'HIS nitiative
y the Examiner. under 35 U.S.C. § 119(a)-(d ve been received.		
• •		tho
oddinents nave been recen	co in this national stage application nom	uie
cation or in an Application E application has been received and the state of this communication to file of this application. THIS THE mitted. Note the attached E was reason(s) why the oath last be submitted. The son's Patent Drawing Review Amendment / Comment of the margin according to 37 to sit of BIOLOGICAL MA	Pata Sheet. 37 CFR 1.78. Pred. Alor 121 since a specific reference was income. It a reply complying with the requirements in a reply complying with the requirements in a reply complying with the requirements. EXAMINER'S AMENDMENT or NOTICE Or or declaration is deficient. EW (PTO-948) attached Ich has been approved by the Examiner. For in the Office action of Paper No the drawings in the front (not the back) of CFR 1.121(d). TERIAL must be submitted. Note the	cluded noted ABLE . F
6∏ Interview S 8), 7⊠ Examiner's	ummary (PTO-413), Paper No Amendment/Comment Statement of Reasons for Allowance Susan S. Lee Primary Examiner	
	Examiner Susan S. Lee Dears on the cover sheet of S. (OR REMAINS) CLOSED of or other appropriate common relights. This application is 3 and MPEP 1308. Dears on the cover sheet of S. (OR REMAINS) CLOSED of or other appropriate common relights. This application is 3 and MPEP 1308. Dears of the Examiner. Dears of the Examiner. Dears of the Examiner of the common received of the common	Divides the attached EXAMINER'S AMENDMENT or NOTICE Of this application. If not the back) of the margin according to 37 CFR 1.121(d). This application is 100 and provided the attached EXAMINER'S Amendment / Comment or in the Office action of Paper No. 1.84(c)) should be written on the drawings in the front (not the back) of the margin according to 37 CFR 1.121(d). National of BIOLOGICAL MATERIAL must be submitted. Note the THE DEPOSIT OF BIOLOGICAL MATERIAL. National of National of Reasons for Allowance 9 □ Other National of National of National Paper No. 1.25

į

EXAMINER'S AMENDMENT

An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.


This application is in condition for allowance except for the presence of claims 3-5 and 31-56 to groups II - VI non-elected without traverse. Accordingly, claims 3-5 and 31-56 have been cancelled. Although applicant has stated that these claims are withdrawn in amendment filed 11/21/03, the status of the claims do not change from withdrawn to cancelled without cancelling them.

The application has been amended as follows:

Please CANCEL claims 3-5 and 31-56 accordance with the following:

1. (previously cancelled)

Art Unit: 2852



Page 3

after excessive oil is removed by means of the carrier-removing roller and before transfer onto printing paper is performed, an electric field is applied in a direction of transfer at such an intensity as not to effect transfer, thereby weakening a force of retaining toner on the image formation surface and thus realizing high efficiency of transfer onto the paper.

3-5. (cancelled)

6. (previously presented) A liquid-development electrophotographic apparatus comprising a development section using a liquid toner as a developer, the development section being in contact with an image bearer body, on which an electrostatic latent image is formed, so as to supply the developer onto the image bearer body, and causing toner particles contained in

Art Unit: 2852

the developer to adhere to the image bearer body according to an electric field established between the development section and the image bearer body to thereby form a toner image; an intermediate transfer section to which the toner image is transferred from the image bearer body; and a transfer-and-fixation section for melting the toner image transferred onto the intermediate transfer section through application of heat at a contact portion between the intermediate transfer section and a printing medium to thereby melt-transfer the toner image onto the printing medium,

wherein the intermediate transfer section is equipped with an excessive-carrier-removing mechanism for removing excessive oil from a toner layer that forms an image on the intermediate transfer section; and

wherein the excessive-carrier-removing mechanism comprises a semiconductive carrier-removing roller or belt which comes into contact with the toner layer heated to not lower than a melting temperature thereof or a temperature near the melting temperature and to which a bias voltage is applied in such a direction as to press toner particles against the intermediate transfer section retaining an image.

- 7. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein the intermediate transfer section comprises a heat roller and an intermediate transfer belt looped around and mounted on the heat roller, for melting the transferred toner image through application of heat to thereby melt-transfer the toner image onto the printing medium; and a plurality of carrier-removing rollers are provided in such a manner as to abut the heat roller.
- 8. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 7, wherein a force which each of the plurality of carrier-removing rollers imposes on the intermediate transfer belt is set individually.
- 9. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 7, wherein a bias voltage with respect to the intermediate transfer belt to be applied to each of the plurality of carrier-removing rollers is set individually.
- 10. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 7, wherein hardness of each of the plurality of carrier-removing rollers is set individually.

Art Unit: 2852

11. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 7, wherein surface hardness of each of the plurality of carrier-removing rollers is set individually.

- 12. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 8, wherein a force which each of the carrier-removing rollers imposes on the intermediate transfer belt is adjusted on the basis of analysis of a print pattern.
- 13. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 9, wherein a bias voltage to be applied to each of the carrier-removing rollers is adjusted on the basis of analysis of a print pattern.
- 14. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 7, wherein the carrier-removing rollers are oriented such that polish grains of the rollers do not disturb an image.
- 15. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, further comprising means for heating the carrier-removing roller and means for detecting temperature of the carrier-removing roller, so as to control the temperature of the carrier-removing roller at a constant level, thereby maintaining the carrier-removing roller at a constant electric resistance for stable carrier removal.
- 16. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein the intermediate transfer section comprises an intermediate transfer roller for superposing toner images in a plurality of colors through transferring the toner images thereto from corresponding image bearer bodies, and an intermediate transfer belt having the superposed toner images transferred thereto at one time from the intermediate transfer roller and functioning to melt the superposed toner images through application of heat at a contact portion between the same and a printing medium to thereby melt-transfer the superposed toner images onto the printing medium, and wherein time required to superpose the toner images in the plurality of colors on the intermediate transfer roller is utilized for controlling a speed of the intermediate transfer belt at the time of melt transfer within such a range as not to affect throughput.

Page 5

Art Unit: 2852

Page 6

17. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 16, wherein the speed of the intermediate transfer belt is controlled such that the intermediate transfer belt is rotated a plurality of times during a time between transfer of the toner images from the intermediate transfer roller to the intermediate transfer belt and melt transfer of the toner images onto the printing medium.

- 18. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 17, further comprising means for monitoring the number of rotations of the intermediate transfer belt and changing a bias voltage to be applied to the carrier-removing roller, according to the number of rotations.
- 19. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 17, further comprising means for monitoring the number of rotations of the intermediate transfer belt and changing a force which the carrier-removing roller imposes on the intermediate transfer belt, according to the number of rotations.
- 20. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein the intermediate transfer section comprises an intermediate transfer roller for superposing toner images in a plurality of colors through transferring the toner images thereto from corresponding image bearer bodies, and an intermediate transfer belt having the superposed toner images transferred thereto at one time from the intermediate transfer roller and functioning to melt the superposed toner images through application of heat at a contact portion between the same and a printing medium to thereby melt-transfer the superposed toner images onto the printing medium, and wherein a surface potential of the intermediate transfer belt retaining a heated toner layer is detected; an amount of residual carrier on the intermediate transfer belt is determined from a table describing a relation of the surface potential to the amount of residual carrier; and when the amount of residual carrier is large, the intermediate transfer belt is rotated two rotations.
- 21. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 20, wherein a plurality of carrier-removing rollers are provided in such a manner as to abut the intermediate transfer belt and such that the carrier-removing rollers can abut and retreat from the intermediate transfer belt independently of one another, and wherein

Art Unit: 2852

the number of carrier-removing rollers abutting the intermediate transfer belt is controlled according to the amount of residual carrier.

Page 7

- 22. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein the intermediate transfer section comprises an intermediate transfer roller for superposing toner images in a plurality of colors through transferring the toner images thereto from corresponding image bearer bodies, and an intermediate transfer belt having the superposed toner images transferred thereto at one time from the intermediate transfer roller and functioning to melt the superposed toner images through application of heat at a contact portion between the same and a printing medium to thereby melt-transfer the superposed toner images onto the printing medium, and wherein a reflection-type optical sensor for detecting gloss whose incident angle of light and reflection angle of light are the same is provided on the intermediate transfer belt retaining the heated toner layer; an amount of residual carrier on the intermediate transfer belt is determined from a reflection output from the optical sensor; and when the amount of residual carrier is large, the intermediate transfer belt is rotated two rotations.
- 23. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 22, wherein a plurality of carrier-removing rollers are provided in such a manner as to abut the intermediate transfer belt and such that the carrier-removing rollers can abut and retreat from the intermediate transfer belt independently of one another, and wherein the number of carrier-removing rollers abutting the intermediate transfer belt is controlled according to the amount of residual carrier.
- 24. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein in order to prevent a change in resistance of the carrier-removing roller caused by partial temperature rise of the carrier-removing roller, the carrier-removing roller is retreated from the intermediate transfer section when the carrier-removing roller faces a region other than a print region or when printing is not performed.
- 25. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein the carrier-removing roller is caused to rotate through contact with the intermediate transfer section, which is heated, to thereby be heated to a certain temperature through thermal conduction.

Art Unit: 2852

Page 8

26. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 25, wherein a resistance of the carrier-removing roller is calculated from voltage and current as measured when the voltage is applied between the carrier-removing roller and the intermediate transfer section while the carrier-removing roller is in contact with the intermediate transfer section, and heating is controlled such that the resistance falls within a predetermined range.

- 27. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein temperature of the carrier-removing roller or temperature of a last carrier-removing roller among a plurality of carrier-removing rollers is set higher than temperature of the intermediate transfer section.
- 28. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein a bias voltage to be applied to the carrier-removing roller is changed according to the number of colors of toner images to be superposed on the intermediate transfer section.
- 29. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein a bias voltage to be applied to the carrier-removing roller is controlled so as to limit current to a low level which does not cause variation in electric potential of the intermediate transfer section to thereby avoid influence of the variation on superposition transfer onto the intermediate transfer section.
- 30. (previously presented) A liquid-development electrophotographic apparatus as described in Claim 6, wherein a blade for scraping off carrier liquid from the carrier-removing roller has a plurality of protrusions projecting gravitationally downward so as to cause the carrier liquid collected at a blade tip to drip promptly.

31-56. (cancelled)

The following is an examiner's statement of reasons for allowance:

Art Unit: 2852

The primary reason for allowance of claim 2 is the inclusion of after excessive oil is removed by means of the carrier-removing roller and before transfer onto printing paper is performed, an electric field is applied in a direction of transfer at such an intensity as not to effect transfer, thereby weakening a force of retaining toner on the image formation surface and thus realizing high efficiency of transfer onto the paper.

This is found in all of claim 2, but not disclosed nor suggested by the prior art of record.

The primary reason for allowance of claims 6-30 is the inclusion of the excessive-carrier-removing mechanism comprises a semiconductive carrier-removing roller or belt which comes into contact with the toner layer heated to not lower than a melting temperature thereof or a temperature near the melting temperature and to which a bias voltage is applied in such a direction as to press toner particles against the intermediate transfer section retaining an image. This is found in all of claims 6-30, but not disclosed nor suggested by the prior art of record.

Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled "Comments on Statement of Reasons for Allowance."

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Susan S. Lee whose telephone number is 703-308-

Art Unit: 2852

2138. The examiner can normally be reached on Mon. - Fri., 10:30-8:00, Second Monday Off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Art Grimley can be reached on 703-308-1373. The fax phone number for the organization where this application or proceeding is assigned is 703-305-3432.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703-308-0956.

Súśan Ś. Ĺee Primary Examiner Art Unit 2852

sl